

Helios™ Platform

Highly Flexible, Programmable Edge Controller



WIND RIVER



BENEFITS

- Select wireless service or wired connectivity, pre-certified and simple to deploy
- Enable your application to meet evolving requirements through the simple to use APIs offered by Everyware™ Software Framework
- Speed time to market for your device on industrial, application-ready platform
- Build to fit from multiple OS and hardware options that ideally match your application

The Eurotech Helios™ edge controller provides a flexible and programmable hardware platform with enhanced wireless connectivity that enables simplified data acquisition and integration. The Helios edge controller could collect data from distributed devices, monitors and sensors; aggregate and rationalize disparate data; and transmit the information to a central processing center. With the Helios platform, you can quickly and simply create an edge controller device, loaded with your application software that precisely meets the needs of your target customers.

The Helios platform offers Four Degrees of Flexibility – programmability, hardware, software, and connectivity. The programmable Helios device offers a simple to use set of APIs enabling you to implement the latest technologies with ease. Hardware flexibility lets you choose the initial device options based on the specs you need to meet, including processor speed, memory capacity, temperature range and video display. Software options include Microsoft Embedded Standard, CE 6.0 or Wind River Linux 3.0 operating systems. Connectivity choices mean you can select pre-certified wireless modules for cellular, Bluetooth, WiFi and others dependent upon technology or carrier preferences.

Start with the Helios platform from Eurotech, and you are well on your way to creating an industrial-grade application device that you can take to market quickly.

Helios™ Platform

Specifications*

PROCESSOR	Intel® Atom™ Z5xx processor at 1.1 GHz (up to 1.6 GHz options) Intel® System Controller Hub US15W (Intel® SCH US15W)
GRAPHICS/VIDEO/AUDIO	Multimedia card support for display and audio options
MEMORY	512 MB DDR-2 DRAM (up to 2 GB options) 2 GB CompactFlash® card (SD card option) On-board PATA flash (option) Internal SATA drive (option)
OPERATING ENVIRONMENTS	Wind River Linux 3.0 Windows® Embedded Standard Windows® CE 6.0
POWER	12V DC (up to 36 V vehicle power input option) TBDW (base system) Power management support capable of operation at < 3W
COMMUNICATIONS AND I/O	USB Bay w. three USB 2.0 host ports (H/F/L speeds) for wireless devices and storage Three external antenna connections to the USB Bay Two general-purpose USB 2.0 host ports (H/F/L speeds) Gigabit Ethernet port EIA-232 or EIA-485 serial port (software-selectable) GPS with external antenna connection (option)
PERIPHERALS	Eight software-controlled LED status indicators Software-readable push-button Battery-backed real-time clock
PHYSICAL	ABS plastic and aluminum enclosure (25.9 x 12.1 x 4.5 cm) Adaptable I/O side plates Removable USB Bay cover Mounting options Extended temperature -40°C to +85°C (0°C to 70°C for 1.6 GHz option)

*Specifications and features subject to change without notice
See our website for latest updates and more information
www.eurotech-inc.com

About Us

Eurotech delivers embedded computer systems for high capability and low power applications, networking and wearable computing solutions, and application framework middleware for multimedia, industrial, transportation, medical, and wireless applications. Eurotech platforms allow OEM and enterprise customers to focus on their core revenue-generating products and services and get to market quickly.

Helios™ and Everyware™ Software Framework are trademarks of Eurotech Group. Other trademarks are property of their respective holders.



Secure USB bay, open view

CMM4516 Sept2009